




Anti Vandal Switch Ø19mm

Order Code



Series	Actuator Options	Terminal Options	Function Options	Material Options	Illumination Style Options	Led- Color Options	Illumination Voltage Options	Graphic Options
☐ ☐	☐	☐	☐	☐	☐	☐	☐	☐ ☐ ☐
L19	F-Flat	NONE-Solder lug (2.8X0.5) N-Screw	M-Momentary 1-1NO1NC Z-Latching 1-1NO1NC	S-Stainless steel A-Anodized aluminum	NONE-Non-illum. D-Dot R-Ring X-Backlit label kit**	NONE-Non-illum. W-White Y-Yellow B-Blue G-Green R-Red O-Orange	NONE-Base voltage* 3.3V 6V 12V 24V 36V 110V 220V	NONE-Non-marking LE-Laser etched

Notes
 * Base voltage on LEDs:
 1.8V @20mA for red, yellow and orange LED colors
 2.8V @20mA for blue, green and white LED colors
 **5 ICON labels included, flat actuator only

Description






Panel Cutout & Illuminated Options



Technical Data

Type	L19-F
Illuminated options	Non-illuminated / Ring illuminated / Dot illuminated / Backlit label kit
Terminal	Screw / Solder lug (2.8X0.5)
Max. switch rating	Ith: 5A Ui: 250VAC
Contact resistance	≤50mΩ
Insulation resistance	≥1000m
Dielectric strength	2000VAC
Operation temp.	-20°C ~ +55°C
Mechanical life	1,000,000 cycles
Electrical life	50,000 cycles
Contact material	Silver alloy
Torque	5~14Nm
Operation pressure	Approx. 5N
Protection	IP65 or IP67 / IK09
Material	
Actuator	Stainless steel / Anodized aluminum
Body	Stainless steel / Anodized aluminum
Base	PA
LED	
Color	3.3V / 6V / 12V / 24V / 36V / 110V / 220V R/G/Y/O/B/W Approx. 40,000 hours

Dimensions



Latching

