



Anti Vandal Switch Ø 12mm

Specifications

Electrical rating: 0.5A/220VDC
Mechanical life: 200,000 Cycles
Electrical life: over 50,000 Cycles
Contact resistance: 50mΩ Max
Insulation resistance: 1000mΩ Min
Dielectric strength: 2000VAC
Operating / Storage temperature: -20°C to 55°C
Travel: 2.50mm
Moisture protection: IP40
Mounting nut torque: 5-14Nm

Features & Benefits

- 10mm diameter panel cutout
- Variety of LED option
- Ring illumination available
- Pilot indicator option
- IP40 rated
- Momentary, Latching
- Terminal option: Solder lug(1.8X0.4)

Order Code

Series	Actuator Options	Function Options	Material Options	Illumination Style Options	Led-Color Options	Illumination Voltage Options
L10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	H-High	M-Momentary 1NO1NC Z-Latching 1NO1NC	S-Stainless Steel	NONE-Non-illuminated R-Ring	NONE-Non-illuminated W-White R-Red O-Orange G-Green B-Blue Y-Yellow	NONE-Base voltage* 6V 12V 24V 110V 220V 6,12, 24,36V are inner resistor, other voltage can be made to order and need to connect an outer resistor.

Notes:

- *Base voltage on LEDs:
 - 1.8V @ 20mA for red, yellow and orange LED colors
 - 2.8V @ 20mA for blue, green and white LED colors

Diameter of Installation Hole

