


Anti Vandal Switch Ø28 mm

Order Code

Series	Actuator Options	Terminal Options	Function Options	Material Options	Illumination Style Options	Led- Color Options	Illumination Voltage Options	Graphic Options
☐ L28	☐ F-Flat	☐ NONE-Solder lug (2.8X0.5)	☐ M-Momentary 1-1NO1NC 2-2NO2NC Z-Latching 1-1NO1NC 2-2NO2NC	☐ S-Stainless steel	☐ NONE-Non-illum. D-Dot R-Ring	☐ NONE-Non-illum. W-White Y-Yellow B-Blue G-Green R-Red O-Orange	☐ NONE-Base voltage** 3.3V 6V 12V 24V 36V 110V 220V	☐ NONE-Non-marking LE-Laser etched

Notes:
 * Base voltage on LEDs:
 1.8V @20mA for red, yellow and orange LED colors
 2.8V @20mA for blue, green and white LED colors


Description



Terminals (-) and (+) used with illum.option only

Panel Cutout & Illuminated Options

自锁 Momentary: L=40mm
 自复 ON-OFF : L=35mm



Technical Data

Type	L28-F
Illuminated options	Non-illuminated / Ring illuminated / Dot illuminated
Terminal	Solder lug (2.8X0.5)
Max. switch rating	Ith: 5A Ui: 250VAC
Contact resistance	≤50mΩ
Insulation resistance	≥1000mΩ
Dielectric strength	2000VAC
Operation temp.	-20°C ~ +55°C
Mechanical life	1,000,000 cycles
Electrical life	> 50,000 cycles
Contact material	Silver alloy
Torque	5~14Nm
Operation pressure	Approx. 8N
Protection	IP67/IK10
Material	
Actuator	Stainless steel
Body	Stainless steel
Base	PA
LED	
Color	3.3V / 6V / 12V / 24V / 36V / 110V / 220V R/G/Y/O/B/W Approx. 40,000 hours