



Anti Vandal Switch $\varnothing$ 40 mm


Order Code

Series	Actuator Options	Terminal Options	Function Options	Material Options	Illumination Style Options	Led- Color Options	Illumination Voltage Options	Graphic Options
☐ ☐	☐	☐	☐	☐	☐	☐	☐ — ☐	☐ ☐ ☐
L40	F-Flat	NONE-Solder lug (2.8X0.5)	M-Momentary 1-1NO1NC Z-Latching 1-1NO1NC	S-Stainless steel	R-Ring	W-White Y-Yellow B-Blue G-Green R-Red O-Orange	NONE-Base voltage** 3.3V 6V 12V 24V 36V 110V 220V	NONE-Non-marking LE-Laser etched

Notes:

* Base voltage on LEDs:
1.8V @20mA for red, yellow and orange LED colors
2.8V @20mA for blue, green and white LED colors

Description



Terminals (-) and (+) used with illum.option only

Technical Data

Type	L40-F
Illuminated options	Ring illuminated
Terminal	Solder lug (2.8X0.5)
Max. switch rating	Ith: 5A Ui: 250VAC
Contact resistance	$\leq 50m\Omega$
Insulation resistance	$\geq 1000m\Omega$
Dielectric strength	2000VAC
Operation temp.	-20°C ~ +55°C
Mechanical life	1,000,000 cycles
Electrical life	> 50,000 cycles
Contact material	Silver alloy
Torque	5~14Nm
Operation pressure	Approx. 8N
Protection	IP67/IK10
Material	
Actuator	Stainless steel
Body	Stainless steel
Base	PA
Color	LED 3.3V / 6V / 12V / 24V / 36V / 110V / 220V R/G/Y/O/B/W Approx, 40,000 hours

自锁 Momentary: L=40mm
自复 ON-OFF : L=35mm

